

Woodtype **PEAR steamed**

Description 3 layers of the same hardwood. Due to the steaming with vitalized Grandier water, the Pear without heartwood receives a warm, reddish brown colour. The sorting Wohngefühl is knotty, with a medium structure.

Brinell hardness 4,5 kp
 Gross density 0,72 g | cm³

1-Strip Country House Flooring PEAR steamed Wohngefühl System board "Madrid"



Surfaces

- Oil | wax oxidative dried
- Varnished 7-times
- Untreated sanded
- Brushed
- Bevel
- Special colour



Symbol picture - may vary in colour and structure

Sorting guidelines	Wohngefühl
Healthy knots	allowed (partly allowed)
Black knots	to approx. 35 mm allowed (partly filled)
Healthy red heart	not allowed
Healthy heartwood	not allowed
Cracks	scattered allowed (partly filled)
Curled spots differences in structure	scattered allowed
Natural differences in colour	allowed
Natural fiber orientation	to 1 3 allowed
Wormholes & insect-ate-spots	not allowed
Sapwood	not allowed
Red or brown spots	scattered allowed
Stains from storage and light blueness	not allowed
Knocked spots	not allowed
Mirror	not allowed

Technical data	
Thickness:	15 mm Useful layer: approx. 5 mm
Width:	150 mm
Length:	Fixed length 1100 mm (8 layers pkg.)
Connection:	Tongue and groove
<div style="display: flex; justify-content: space-around;"> <div style="border: 1px solid black; padding: 5px;">m² pkg. 1,32</div> <div style="border: 1px solid black; padding: 5px;">m² pal. 64,68</div> </div>	
<div style="display: flex; justify-content: space-around;"> <div style="border: 1px solid black; padding: 5px;">kg pkg. 12</div> <div style="border: 1px solid black; padding: 5px;">kg pal. 588</div> </div>	
<input checked="" type="checkbox"/> Floating laying <input checked="" type="checkbox"/> Glued laying <input checked="" type="checkbox"/> Suitable for underfloor heating when gluing the entire area with solvent-free adhesives	



Woodtype **PEAR steamed**

Description 3 layers of the same hardwood. Due to the steaming with vitalized Grander water, the Pear with partial heartwood receives a warm, reddish brown colour. The sorting Design ist slightly to very knotty, with a medium structure.

Brinell hardness 4,5 kp
 Gross density 0,72 g | cm³

1-Strip Country House Flooring PEAR steamed Design System board "Lissabon"



Surfaces

- Oil | wax oxidative dried
- Varnished 7-times
- Untreated sanded
- Brushed
- Bevel
- Special colour



Symbol picture - may vary in colour and structure

Sorting guidelines	Design
Healthy knots	allowed (partly filled)
Black knots	allowed (partly filled)
Healthy red heart	allowed
Healthy heartwood	allowed
Cracks	allowed (partly filled)
Curled spots differences in structure	allowed
Natural differences in colour	allowed
Natural fiber orientation	allowed
Wormholes & insect-ate-spots	not allowed
Sapwood	not allowed
Red or brown spots	allowed
Stains from storage and light blueness	allowed
Knocked spots	not allowed
Mirror	allowed

Technical data					
Thickness:	15 mm Useful layer: approx. 5 mm				
Width:	150 mm				
Length:	Fixed length 1100 mm (8 layers pkg.)				
Connection:	Tongue and groove				
<table border="1" style="width: 100%;"> <tr> <td>m² pkg. 1,32</td> <td>m² pal. 64,68</td> </tr> <tr> <td>kg pkg. 12</td> <td>kg pal. 588</td> </tr> </table>		m² pkg. 1,32	m² pal. 64,68	kg pkg. 12	kg pal. 588
m² pkg. 1,32	m² pal. 64,68				
kg pkg. 12	kg pal. 588				
<input checked="" type="checkbox"/> Floating laying <input checked="" type="checkbox"/> Glued laying <input checked="" type="checkbox"/> Suitable for underfloor heating when gluing the entire area with solvent-free adhesives					



Symbol picture - may vary in colour and structure

Woodtype **PEAR steamed**

Description 3 layers of the same hardwood. Due to the steaming with vitalized Grander water, the Pear without heartwood receives a warm, reddish brown colour. The sorting Klassiker is essentially knot-free*, with a simple structure.

Brinell hardness 4,5 kp
 Gross density 0,72 g | cm³

2-Strip Plank Flooring PEAR steamed "Klassiker"



Surfaces

- Oil | wax oxidative dried
- Varnished 7-times
- Untreated sanded
- Special colour



Symbol picture - may vary in colour and structure

Sorting guidelines	Klassiker
Healthy knots	till ø 5 mm allowed
Black knots	till ø 5 mm allowed
Healthy red heart	not allowed
Healthy heartwood	not allowed
Cracks	not allowed
Curled spots differences in structure	scattered allowed
Natural differences in colour	slightly allowed
Natural fiber orientation	allowed
Wormholes & insect-ate-spots	not allowed
Sapwood	not allowed
Red or brown spots	not allowed
Stains from storage and light blueness	not allowed
Knocked spots	not allowed
Mirror	not allowed

Technical data					
Thickness:	15 mm Useful layer: approx. 5 mm				
Width:	140 mm				
Length:	Fixed length 2400 mm (8 layers pkg.)				
Connection:	Tongue and groove				
<table border="1" style="width: 100%;"> <tr> <td>m² pkg. 2,69</td> <td>m² pal. 112,98</td> </tr> <tr> <td>kg pkg. 26,2</td> <td>kg pal. 1104</td> </tr> </table>		m² pkg. 2,69	m² pal. 112,98	kg pkg. 26,2	kg pal. 1104
m² pkg. 2,69	m² pal. 112,98				
kg pkg. 26,2	kg pal. 1104				
<input checked="" type="checkbox"/> Floating laying <input checked="" type="checkbox"/> Glued laying <input checked="" type="checkbox"/> Suitable for underfloor heating when gluing the entire area with solvent-free adhesives					



Woodtype	PEAR steamed
Description	3 layers of the same hardwood. Due to the steaming with vitalized Grander water, the Pear without heartwood receives a warm, reddish brown colour. The sorting Trend-Epoca is knotty, with a lively structure.
Brinell hardness	4,5 kp
Gross density	0,72 g cm³

2-Strip Plank Flooring PEAR steamed "Trend-Epoca"



Surfaces

- Oil | wax oxidative dried
- Varnished 7-times
- Untreated sanded
- Special colour



Symbol picture - may vary in colour and structure

Sorting guidelines	Trend-Epoca
Healthy knots	allowed (partly filled)
Black knots	allowed (partly filled)
Healthy red heart	not allowed
Healthy heartwood	not allowed
Cracks	allowed (partly filled)
Curled spots differences in structure	allowed
Natural differences in colour	allowed
Natural fiber orientation	allowed
Wormholes & insect-ate-spots	not allowed
Sapwood	not allowed
Red or brown spots	allowed
Stains from storage and light blueness	allowed
Knocked spots	not allowed
Mirror	not allowed

Technical data					
Thickness:	15 mm				
Width:	140 mm				
Length:	Fixed length 2400 mm (8 layers pkg.)				
Connection:	Tongue and groove				
<table border="0" style="width: 100%;"> <tr> <td style="border: 1px solid black; padding: 5px;">m² pkg. 2,69</td> <td style="border: 1px solid black; padding: 5px;">m² pal. 112,98</td> </tr> <tr> <td style="border: 1px solid black; padding: 5px;">kg pkg. 26,2</td> <td style="border: 1px solid black; padding: 5px;">kg pal. 1104</td> </tr> </table>		m² pkg. 2,69	m² pal. 112,98	kg pkg. 26,2	kg pal. 1104
m² pkg. 2,69	m² pal. 112,98				
kg pkg. 26,2	kg pal. 1104				
<input checked="" type="checkbox"/> Floating laying <input checked="" type="checkbox"/> Glued laying <input checked="" type="checkbox"/> Suitable for underfloor heating <small>when gluing the entire area with solvent-free adhesives</small>					

