

TYPES OF WOOD ALDER natural|steamed - ASH - BEECH natural|steamed - BIRCH  
 BLACK WALNUT steamed - CHERRY natural|steamed - ELM steamed  
 MAPLE - OAK - PEAR steamed - **SMOKED OAK** - SMOKED ZIRNOAK



THE LUXURY CLASS

Woodtype

## SMOKED OAK european heartsmoked

**Description** 3 layers of hardwood. The European Oak receives a blackish-brown colour due to a special fumigation procedure. The sorting Design is slightly to very knotty, with a lively structure and naturally colour differences.

Brinell hardness 4,2 kp  
 Gross density 0,71 g|cm³

### 1-Strip Country House Flooring SMOKED OAK european Design „Cube”



Fixlength 600 or 750 mm

#### SURFACES

- ☒ Oil | wax oxidative dried
- ☒ Untreated sanded
- ☒ Brushed
- ☒ Special colour



Symbol picture - may vary in colour and structure

[www.bergland-parkett.at](http://www.bergland-parkett.at)

#### Sorting guidelines

|  |   |
|--|---|
| Healthy knots                            | allowed (partly filled)   |
| Black knots                              | allowed (partly filled)   |
| Healthy red heart                        | not allowed   |
| Healthy black heart                      | not allowed   |
| Cracks                                   | allowed (partly filled)   |
| Curlled Spots   differences in structure | allowed   |
| Natural colour differences               | allowed   |
| Natural fiber orientation                | allowed   |
| Wormholes and insect-ate-spots           | not allowed <small>are allowed in middle layer and back layer**</small> |
| Sapwood                                  | partly allowed  |
| Red or brown spots                       | allowed   |
| Stains from storage and light blueness   | allowed   |
| Knocked spots                            | not allowed   |
| Mirror                                   | alongside and crosswise allowed   |

#### Technical data

|                                 |                      |   |
|---------------------------------|----------------------|---|
| Thickness                       | 15 mm                | Useful layer approx. 5 mm   |
| Width                           | 150 mm               |   |
| Length                          | Side length          | 600 x 600* mm<br>750 x 750** mm   |
|                                 | Cube elements        | right & left elements   |
| Ensure an even number per order |                      |   |
| Connection                      | Tongue and groove    | Due to the technical drying, there are no longer any pests, only the holes in the middle layer and back layer** |
| Quantity                        | Example with 200 pcs |   |

m² | pkg. 0,36\* | 0,56\*\*

m² | pal. 72\* | 112\*\*

kg | pkg. 2,5\* | 3,3\*\*

kg | pal. 500\* | 670\*\*

☒ Glued laying

☒ Suitable for underfloor heating  
 when gluing the entire area with solvent-free adhesives

