

Woodtype **ASH**

Description 3 layers of the same hardwood. The Ash with heartwood has a light yellow to slightly brownish to prominent dark brown colour. The sorting Design is slightly to very knotty, with a lively structure.

Brinell hardness 4,5 kp  
 Gross density 0,69 g | cm³

## 1-Strip Country House Flooring ASH Design „Melk” W150



### SURFACES

- Oil | wax oxidative dried
- Varnished 7-times
- Untreated sanded
- Bevel
- Special colour

### also available as

- Systemboard  
(Fixlength 1100 mm)



[www.bergland-parkett.at](http://www.bergland-parkett.at)

| Sorting guidelines                       |                         |
|--|-------------------------|
| Healthy knots                            | allowed (partly filled) |
| Black knots                              | allowed (partly filled) |
| Healthy red heart                        | allowed                 |
| Healthy black heart                      | allowed                 |
| Cracks                                   | allowed (partly filled) |
| Curlted Spots   differences in structure | allowed                 |
| Natural colour differences               | allowed                 |
| Natural fiber orientation                | allowed                 |
| Wormholes and insect-ate-spots           | not allowed             |
| Sapwood                                  | not allowed             |
| Red or brown spots                       | allowed                 |
| Stains from storage and light blueness   | allowed                 |
| Knocked spots                            | not allowed             |
| Mirror                                   | not allowed             |

| Technical data   |                   |                           |
|--|-------------------|---------------------------|
| Thickness  | 15 mm             | Useful layer approx. 5 mm |
| Width  | 150 mm            |                           |
| Length   | Lengthsystem      | 6 layers 1900 mm          |
|  | (8 layers   pkg)  | 2 layers 950* mm          |
| Connection   | Tongue and groove |                           |
| One layer 950* mm consists of 2 boards                                 |                   |                           |
| m²   pkg. 2,28   |                   | m²   pal. 111,72          |
| kg   pkg. 23   |                   | kg   pal. 1127            |
| <input checked="" type="checkbox"/> Floating laying                    |                   |                           |
| <input checked="" type="checkbox"/> Glued laying                       |                   |                           |
| <input checked="" type="checkbox"/> Suitable for underfloor heating    |                   |                           |
| <small>when gluing the entire area with solvent-free adhesives</small> |                   |                           |

