BLACK WALNUT steamed - CHERRY natural|steamed - ELM steamed

MAPLE - OAK - PEAR steamed - SMOKED OAK - SMOKED ZIRNOAK



Woodtype ASH

Description 3 layers of the same hardwood. The Ash without heartwood has a light yellow to

slightly brownish colour. The sorting Auslese is essentially knot-free*, with a simple struc-

ture.

Brinell hardness 4,5 kp Gross density 0,69 g | cm³

1-Strip Country House Flooring ASH Auslese "St.Pölten"



SURFACES

- Oil | wax oxidative dried
- ✓ Varnished 7-times
- ✓ Untreated sanded
- **▼** Bevel
- ✓ Special colour



www.bergland-parkett.at

Sorting guidelines	
Healthy knots	to approx. 5 mm allowed
Black knots	to approx. 5 mm allowed
Healthy red heart	not allowed
Healthy black heart	not allowed
Cracks	not allowed
Curled Spots differences in structure	slightly allowed
Natural colour differences	slightly allowed
Natural fiber orientation	slightly allowed
Wormholes and insect-ate-spots	not allowed
Sapwood	not allowed
Red or brown spots	not allowed
Stains from storage and light blueness	not allowed
Knocked spots	not allowed
Mirror	not allowed

-		 	
Tec	hn		ata
15.			

Thickness 15 mm Useful layer approx. 5 mm

Width 150 mm

Length Lengthsystem 6 layers 1900 mm

(8 layers | pkg) 2 layers 950* mm

Connection Tongue and groove

One layer 950* mm consists of 2 boards

m² | pkg. 2,28 | m² | pal. 111,72

kg|pkg. 23 | kg|pal. 1127

✓ Floating laying

Glued laying

Suitable for underfloor heating when gluing the entire area with solvent-free adhesives

