

Woodtype

BEECH steamed

Description 3 layers of the same hardwood. Due to the steaming with vitalized Grander water, the Beech receives a light, slightly reddish to deep reddish brown colour. The sorting Design is slightly to very knotty, with a lively structure.

Brinell hardness 4,0 kp
 Gross density 0,72 g | cm³

1-Strip Country House Flooring BEECH steamed Design „Dornbirn“



SURFACES

- Oil | wax oxidative dried
- Varnished 7-times
- Untreated sanded
- Bevel
- Special colour



www.bergland-parkett.at

Symbol picture - may vary in colour and structure

Sorting guidelines	
Healthy knots	allowed (partly filled)
Black knots	allowed (partly filled)
Healthy red heart	allowed
Healthy black heart	allowed
Cracks	allowed (partly filled)
Curlted Spots differences in structure	allowed
Natural colour differences	allowed
Natural fiber orientation	allowed
Wormholes and insect-ate-spots	not allowed
Sapwood	not allowed
Red or brown spots	allowed
Stains from storage and light blueness	allowed
Knocked spots	not allowed
Mirror	allowed

Technical data		
Thickness	15 mm	Useful layer approx. 5 mm
Width	150 mm	
Length	Lengthsystem (8 layers pkg)	6 layers 1900 mm 2 layers 950* mm
Connection	Tongue and groove	
One layer 950* mm consists of 2 boards		
m ² pkg. 2,28		m ² pal. 111,72
kg pkg. 23		kg pal. 1127
<input checked="" type="checkbox"/> Floating laying		
<input checked="" type="checkbox"/> Glued laying		
<input checked="" type="checkbox"/> Suitable for underfloor heating when gluing the entire area with solvent-free adhesives		

