BLACK WALNUT steamed - CHERRY natural|steamed - ELM steamed

MAPLE - OAK - PEAR steamed - SMOKED OAK - SMOKED ZIRNOAK



Woodtype BEECH steamed

Description 3 layers of the same hardwood. Due to the steaming with vitalized Grander wa-

ter, the Beech without heartwood receives a light, slightly reddish to deep reddish

brown colour. The sorting Trend-Epoca is knotty, with a lively structure.

Brinell hardness 4,0 kp Gross density 0,72 g | cm³

2-Strip Plank Flooring BEECH steamed "Trend-Epoca"



Oil | wax oxidative dried

✓ Varnished 7-times

✓ Untreated sanded

▼ Bevel



www.bergland-parkett.at

Sorting guidelines	
Healthy knots	allowed (partly filled)
Black knots	allowed (partly filled)
Healthy red heart	not allowed
Healthy black heart	not allowed
Cracks	allowed (partly filled)
Curled Spots differences in structure	allowed
Natural colour differences	allowed
Natural fiber orientation	allowed
Wormholes and insect-ate-spots	not allowed
Sapwood	not allowed
Red or brown spots	allowed
Stains from storage and light blueness	allowed
Knocked spots	not allowed
Mirror	allowed

-				
	hr	2100	ıl data	
15.		11(. (1		

Thickness 15 mm Useful layer approx. 5 mm

Width 140 mm

(8 layers | pkg)

Length Fixlength 8 layers 2400 mm

Connection Tongue and groove

m² | pkg. 2,69 | m² | pal. 112,98

kg|pkg. 26,2 | kg|pal. 1104

✓ Floating laying

Glued laying

Suitable for underfloor heating when gluing the entire area with solvent-free adhesives

