

TYPES OF WOOD ALDER natural|steamed - ASH - BEECH natural|steamed - BIRCH
BLACK WALNUT steamed - CHERRY natural|steamed - ELM steamed
MAPLE - OAK - PEAR steamed - **SMOKED OAK** - SMOKED ZIRNOAK



THE LUXURY CLASS

Woodtype

SMOKED OAK european heart-smoked

Description 3 layers of hardwood. The European Oak receives a blackish-brown colour due to a special fumigation procedure. Special features are the naturally occurring colour differences (light | dark). The sorting Ambiente is slightly to very knotty, with a lively structure.

Brinell hardness 4,2 kp

Gross density 0,71 g | cm³

The creative program consists of 3 layers hardwood, where the middle layer and the under layer can vary to the top layer.

1-Strip Country House Flooring SMOKED OAK european Ambiente „Luzern“ Kreativ



SURFACES

☒ Oil | wax oxidative dried



www.bergland-parkett.at

Symbol picture - may vary in colour and structure

Sorting guidelines

Healthy knots	allowed (partly filled)
Black knots	allowed (partly filled)
Healthy red heart	not allowed
Healthy black heart	not allowed
Cracks	allowed (partly filled)
Curled Spots differences in structure	allowed
Natural colour differences	allowed
Natural fiber orientation	allowed
Wormholes and insect-ate-spots	not allowed <small>are allowed in middle layer and back layer**</small>
Sapwood	partly allowed
Red or brown spots	allowed
Stains from storage and light blueness	allowed
Knocked spots	not allowed
Mirror	alongside and crosswise allowed

Technical data

Thickness	10,7 mm	Useful layer approx. 3 mm
Width	150 mm	
Length	Lengthsystem (11 layers pkg)	7 layers 1900 mm 4 layers 950* mm

Connection Tongue and groove Due to the technical drying, there are no longer any pests, only the holes in the middle layer and back layer**

One layer 950* mm consists of 2 boards

m² | pkg. 3,14

m² | pal. 109,90

kg | pkg. 23

kg | pal. 805

☒ **Glued laying.** Prescribed according to the EU standard. Floating installation is technically possible

☒ **Suitable for underfloor heating**
when gluing the entire area with solvent-free adhesives

