

TYPES OF WOOD ALDER natural|steamed - ASH - BEECH natural|steamed - BIRCH  
 BLACK WALNUT steamed - CHERRY natural|steamed - ELM steamed  
 MAPLE - OAK - PEAR steamed - SMOKED OAK - SMOKED ZIRNOAK



THE LUXURY CLASS

Woodtype

## OAK european

**Description** 3 layers of the same hardwood. The European Oak has a middle brown to intensive brown colour. The sorting Trend-Epoca is knotty, with a lively structure.

Brinell hardness 4,2 kp  
 Gross density 0,71 g | cm³

## 2-Strip Plank Flooring OAK european „Trend-Epoca” white



### SURFACES

- ☒ Oil | wax oxidative dried
- ☒ Varnished 7-times
- ☒ Brushed
- ☒ Special colour white



[www.bergland-parkett.at](http://www.bergland-parkett.at)

Symbol picture - may vary in colour and structure

### Sorting guidelines

|   |                                 |
|---|---------------------------------|
| Healthy knots                           | allowed (partly filled)         |
| Black knots                             | allowed (partly filled)         |
| Healthy red heart                       | not allowed                     |
| Healthy black heart                     | not allowed                     |
| Cracks                                  | allowed (partly filled)         |
| Curled Spots   differences in structure | allowed                         |
| Natural colour differences              | allowed                         |
| Natural fiber orientation               | allowed                         |
| Wormholes and insect-ate-spots          | not allowed                     |
| Sapwood                                 | partly allowed                  |
| Red or brown spots                      | allowed                         |
| Stains from storage and light blueness  | allowed                         |
| Knocked spots                           | not allowed                     |
| Mirror                                  | alongside and crosswise allowed |

### Technical data

|           |                  |                           |
|-----------|------------------|---------------------------|
| Thickness | 15 mm            | Useful layer approx. 5 mm |
| Width     | 140 mm           |                           |
| Length    | Fixlength        | 8 layers 2400 mm          |
|           | (8 layers   pkg) |                           |

Connection Tongue and groove

m² | pkg. 2,69

m² | pal. 112,98

kg | pkg. 26,2

kg | pal. 1104

☒ Floating laying

☒ Glued laying

☒ Suitable for underfloor heating

when gluing the entire area with solvent-free adhesives



Symbol picture - may vary in colour and structure