BLACK WALNUT steamed - CHERRY natural|steamed - ELM steamed

MAPLE - OAK - PEAR steamed - SMOKED OAK - SMOKED ZIRNOAK



Woodtype OAK european

Description 3 layers of the same hardwood. The European Oak has a middle brown to

intensive brown colour. The sorting Klassiker is essentially knot-free\*, with a simple

structure.

Brinell hardness 3,2 kp Gross density 0,63 g | cm³

## 2-Strip Plank Flooring european OAK "Klassiker"



## **SURFACES**

- Oil | wax oxidative dried
- ✓ Varnished 7-times
- ✓ Untreated sanded
- ✓ Brushed
- ✓ Special colour



www.bergland-parkett.at

| Sorting guidelines                      |                                 |
|---|---------------------------------|
| Healthy knots                           | to approx. 5 mm allowed         |
| Black knots                             | to approx. 5 mm allowed         |
| Healthy red heart                       | not allowed                     |
| Healthy black heart                     | not allowed                     |
| Cracks                                  | not allowed                     |
| Curled Spots   differences in structure | partly allowed                  |
| Natural colour differences              | slightly allowed                |
| Natural fiber orientation               | partly allowed                  |
| Wormholes and insect-ate-spots          | not allowed                     |
| Sapwood                                 | not allowed                     |
| Red or brown spots                      | not allowed                     |
| Stains from storage and light blueness  | not allowed                     |
| Knocked spots                           | not allowed                     |
| Mirror                                  | alongside and crosswise allowed |

## Technical data

Thickness 15 mm Useful layer approx. 5 mm

Width 140 mm

Length Fixlength 8 layers 2400 mm

(8 layers | pkg)

Connection Tongue and groove

m<sup>2</sup> | pkg. 2,69 | m<sup>2</sup> | pal. 112,98

kg|pkg. 26,2 | kg|pal. 1104

 ✓ Floating laying

Glued laying

✓ Suitable for underfloor heating when gluing the entire area with solvent-free adhesives

