

1-Strip Country House Flooring MAPLE european Design "Hallstatt"



SURFACES

- Oil | Wax oxidative dried
- Varnished 7-times
- ✓ Untreated sanded
- 🗹 Bevel
- Special colour



www.bergland-parkett.at

Sorting guidelines	
Healthy knots	allowed (partly filled)
Black knots	allowed (partly filled)
Healthy red heart	allowed
Healthy black heart	allowed
Cracks	allowed (partly filled)
Curled Spots differences in structure	allowed
Natural colour differences	allowed
Natural fiber orientation	allowed
Wormholes and insect-ate-spots	not allowed
Sapwood	not allowed
Red or brown spots	allowed
Stains from storage and light blueness	allowed
Knocked spots	not allowed
Maple bar	alongside and crosswise allowed

TAC	hnical	data
IEC	mucu	uulu

Thickness 15 mm Width 150 mm Length Lengthsystem (8 layers | pkg)

Useful layer approx. 5 mm

6 layers 1900 mm

2 layers 950* mm

Connection Tongue and groove

One layer 950* mm consists of 2 boards

m² pkg. 2,28	m² pal. 111,72	
kg pkg. 23	kg pal. 1127	
✓ Floating laying		
☑ Glued laying		

Suitable for underfloor heating when gluing the entire area with solvent-free adhesives

