BLACK WALNUT steamed - CHERRY natural|steamed - ELM steamed

MAPLE - OAK - PEAR steamed - SMOKED OAK - SMOKED ZIRNOAK



OAK european

Description 3 layers of hardwood. The European Oak has a middle brown to intensive brown

colour. The sorting Desing is slightly to very knotty, with a lively structure and natu-

rally differences of colour.

Brinell hardness 4,2 kp Gross density 0,71 g | cm³

## 1-Strip Country House Flooring OAK european Design Bergland-Point 55°





## **SURFACES**

Oil | Wax oxidative dried

✓ Brushed



www.bergland-parkett.at

Sorting guidelines		
Healthy knots	allowed (partly filled)	
Black knots	allowed (partly filled)	
Healthy red heart	not allowed	
Healthy black heart	not allowed	
Cracks	not allowed	
Curled Spots   differences in structure	allowed	
Natural colour differences	allowed	
Natural fiber orientation	allowed	
Wormholes and insect-ate-spots	not allowed are allowed in middle layer and back layer.	
Sapwood	not allowed	
Red or brown spots	allowed	
Stains from storage and light blueness	not allowed	
Knocked spots	not allowed	
Mirror	alongside and crosswise allowed	

_					
	$\sim$ h	nic	$\sim$ $\sim$ 1	$\alpha$	ata
	( . I I	1111	. ( 11	( ) (	11(1

Thickness 15 mm Useful layer approx. 5 mm

Width 150 mm

Length Fixlength 8 layers 1020 mm

Extra tongue 2-3 pieces 980x14x4 mm

Connection Tongue and groove Due to the technical drying, there are no longer any pests, only the holes in the middle layer and back layer\*\*

m² | Pkg. 1,22 | m² | Pal. 59,78

kg|Pkg. 12 kg|Pal. 588

✓ Glued laying

✓ Suitable for underfloor heating when gluing the entire area with solvent-free adhesives

