

Woodtype

BLACK WALNUT steamed

Description 3 layers of the same hardwood. Due to the steaming with vitalized Grander water, the Black Walnut receives a light brown to intensive dark brown colour. The special feature is the occasional occurring sapwood. The sorting Ambiente is slightly to medium knotty, with a lively structure.

Brinell hardness 3,4 kp
Gross density 0,64 g | cm³

1-Strip Country House Flooring BLACK WALNUT steamed Ambiente City Star „Prag“



SURFACES

- Oil | wax oxidative dried
- Varnished 7-times
- Untreated sanded
- Bevel
- Special colour

also available as

- 2-Lengthsystem
- Ladder optic
- Herringbone 950 mm



Symbol picture - may vary in colour and structure

www.bergland-parkett.at

Sorting guidelines

Healthy knots	to approx. 10 mm allowed (partly filled)
Black knots	to approx. 10 mm allowed (partly filled)
Healthy red heart	not allowed
Healthy black heart	not allowed
Cracks	not allowed
Curlted Spots differences in structure	allowed
Natural colour differences	allowed
Natural fiber orientation	allowed
Wormholes and insect-ate-spots	not allowed
Sapwood	allowed
Red or brown spots	not allowed
Stains from storage and light blueness	not allowed
Knocked spots	not allowed
Mirror	not allowed

Technical data

Thickness	15 mm	Useful layer approx. 5 mm
Width	120 mm	
Length	Lengthsystem	5 layers 1900 mm
	(8 layers pkg)	3 layers 950* mm
	Lengthsystem	6 layers 950 mm
	(8 layers pkg)	2 layers 475* mm

Connection Tongue and groove
One layer 950* | 475** mm consists of 2 boards

m² | pkg. 0,91•• | 1,83•

m² | pal. 50,96•• | 102,48•

kg | pkg. 9•• | 18•

kg | pal. 504•• | 1008•

Floating laying

Glued laying

Suitable for underfloor heating

when gluing the entire area with solvent-free adhesives

