

Woodtype

BLACK WALNUT steamed

Description 3 layers of the same hardwood. Due to the steaming with vitalized Grander water, the Black Walnut receives a light brown to intensive dark brown colour. A special feature is the proportion of sapwood. The Ambiente grade is slightly to very knotty with a lively structure.

Brinell hardness 3,4 kp
Gross density 0,64 g | cm³

1-Strip Country House Flooring BLACK WALNUT steamed Ambiente „Stams”



SURFACES

- Oil | wax oxidative dried
- Varnished 7-times
- Untreated sanded

also available as

- Systemboard
(Fixlength 950 mm)
Width 145 mm



Symbol picture - may vary in colour and structure

www.bergland-parkett.at

Sorting guidelines

Healthy knots	allowed (partly filled)
Black knots	allowed (partly filled)
Healthy red heart	not allowed
Healthy black heart	not allowed
Cracks	allowed (partly filled)
Curlt Spots differences in structure	allowed
Natural colour differences	allowed
Natural fiber orientation	allowed
Wormholes and insect-ate-spots	not allowed
Sapwood	allowed
Red or brown spots	allowed
Stains from storage and light blueness	allowed
Knocked spots	not allowed
Mirror	not allowed

Technical data

Thickness	15 mm	Useful layer approx. 5 mm
Width	150 mm	
Length	Lengthsystem	5 layers 1900 mm
	(8 layers pkg)	3 layers 950* mm
	Systemboard	8 layers 950 mm
Connection	Tongue and groove	

One layer 950* mm consists of 2 boards

m² | pkg. 2,28 | 1,10**

m² | pal. 111,72 | 53,90**

kg | pkg. 23 | 11**

kg | pal. 1127 | 539**

Floating laying

Glued laying

Suitable for underfloor heating

when gluing the entire area with solvent-free adhesives

