| TYPES OF WOOD | ALDER natural steamed - ASH - BEECH natural steamed - BIRCH BLACK WALNUT steamed - CHERRY natural steamed - ELM steamed MAPLE - OAK - PEAR steamed - SMOKED OAK - SMOKED ZIRNOAK | PARKETT |
|-----------------------------------|---|---------|
| Woodtype | ASH | |
| Description | 3 layers of the same hardwood. The Ash with heartwood has a light yellow to slightly brownish to prominent dark brown colour. The sorting Trend-Epoca is knotty, with a lively structure. | |
| Brinell hardness Gross density | 4,5 kp 0,69 g cm³ | |

2-Strip Plank Flooring ASH "Trend-Epoca"



SURFACES

- Oil | wax oxidative dried
- ✓ Varnished 7-times
- Colour granite grey



www.bergland-parkett.at

| Sorting guidelines | | | |
|---|-------------------------|--|--|
| Healthy knots | allowed (partly filled) | | |
| Black knots | allowed (partly filled) | | |
| Healthy red heart | allowed | | |
| Healthy black heart | allowed | | |
| Cracks | allowed (partly filled) | | |
| Curled Spots differences in structure | allowed | | |
| Natural colour differences | allowed | | |
| Natural fiber orientation | allowed | | |
| Wormholes and insect-ate-spots | not allowed | | |
| Sapwood | not allowed | | |
| Red or brown spots | allowed | | |
| Stains from storage and light blueness | allowed | | |
| Knocked spots | not allowed | | |
| Mirror | not allowed | | |

| Technical data | | | | | |
|--|----------------------------|---------------------------|--|--|--|
| | 5 mm 40 mm | Useful layer approx. 5 mm | | | |
| 0 | xlength 3 layers pkg) | 8 layers 2400 mm | | | |
| Connection Tongue and groove | | | | | |
| m² pkg. 2, | .69 | m² pal. 112,98 | | | |
| kg pkg. 26 | 6,2 | kg pal. 1104 | | | |
| ✓ Floating laying | | | | | |
| ☑ Glued laying | | | | | |
| Suitable for underfloor heating when gluing the entire area with solvent-free adhesives | | | | | |

