

1-Strip Country House Flooring SMOKED OAK european Design "herringbone"



SURFACES

- Oil | Wax oxidative dried
- ✓ Varnished 7-times
- ✓ Untreated sanded
- ☑ Brushed
- 🗹 Bevel
- \checkmark Special colour



www.bergland-parkett.at

Sorting guidelines		Technical data				
Healthy knots	allowed (partly filled)	TI	hickness	15 mm	Useful layer approx. 5 mm	
Black knots	allowed (partly filled)	V	Vidth	150 mm		
Healthy red heart	not allowed	L	ength	Fixlength	8 layers 1100* mm	
Healthy black heart	not allowed			(8 layers pkg)	Or	
Cracks	allowed (partly filled)				8 layers 475** mm	
Curled Spots differences in structure	allowed	C	Connection	Tongue and groc	DVE Due to the technical drying, there are no longer any pests, only the holes in the middle layer and back	
Natural colour differences	allowed	0	One layer 475* mm consists of 2 boards layer**			
Natural fiber orientation	allowed		m² pkg.	1,14** 1,32*	m² pal. 55,90** 64,68*	
Wormholes and insect-ate-spots	not allowed are allowed in middle layer and back layer**			11**110*		
Sapwood	not allowed		kg pkg.	** 2*	kg pal. 539** 588*	
Red or brown spots	allowed	V	☑ Floating laying			
Stains from storage and light blueness	allowed	V	☑ Glued laying			
Knocked spots	not allowed	V	\blacksquare Suitable for underfloor heating			
Mirror	alongside and crosswise allowed		when gluing the entire area with solvent-free adhesives			

