

Woodtype

OAK european

Description 3 layers of the same hardwood. The European Oak has a middle brown to intensive brown colour. The sorting Emotion is essentially knot-free*, with a medium structure.

Brinell hardness 4,2 kp
 Gross density 0,71 g | cm³

1-Strip Country House Flooring OAK european Emotion „Wien-Oberlaa“ W190



SURFACES

- Oil | wax oxidative dried
- Varnished 7-times
- Untreated sanded
- Brushed
- Special colour



Symbol picture - may vary in colour and structure

www.bergland-parkett.at

Sorting guidelines

Healthy knots	to approx. 5 mm allowed (partly filled)
Black knots	to approx. 5 mm allowed (partly filled)
Healthy red heart	not allowed
Healthy black heart	not allowed
Cracks	slightly allowed (partly filled)
Curlted Spots differences in structure	allowed
Natural colour differences	allowed
Natural fiber orientation	to one-third allowed
Wormholes and insect-ate-spots	not allowed <small>are allowed in middle layer and back layer**</small>
Sapwood	not allowed
Red or brown spots	slightly allowed
Stains from storage and light blueness	not allowed
Knocked spots	not allowed
Mirror	alongside and crosswise allowed

Technical data

Thickness	15 mm	Useful layer approx. 5 mm
Width	190 mm	
Length	Lengthsystem (6 layers pkg)	5 layers 1900 mm 1 layer 950* mm
Connection	Tongue and groove	<small>Due to the technical drying, there are no longer any pests, only the holes in the middle layer and back layer**</small>
<small>One layer 950* mm consists of 2 boards</small>		

m² | pkg. 2,17

m² | pal. 97,65

kg | pkg. 22

kg | pal. 990

Floating laying

Glued laying

Suitable for underfloor heating
when gluing the entire area with solvent-free adhesives

