TYPES OF WOOE	ALDER natural steamed - ASH - BEECH natural steamed - BIRCH BLACK WALNUT steamed - CHERRY natural steamed - ELM steamed MAPLE - OAK - PEAR steamed - SMOKED OAK - SMOKED ZIRNOAK	PARKETT
Woodtype	OAK european	
Description	3 layers of the same hardwood. The European Oak has a middle brown to in- tensive brown colour. Special features are the naturally grown, numerous knots. The sorting Ambiente is medium to very knotty, with a lively structure.	
Brinell hardness Gross density	4,2 kp 0,71 g cm³	

1-Strip Country House Flooring OAK european Ambiente "Rust" W190



SURFACES

Oil | wax oxidative dried ☑ Brushed 🗹 Bevel



www.bergland-parkett.at

Sorting guidelines		Technical data		
Healthy knots	allowed (filled)	Thickness 15 mm Useful layer approx. 5 mm		
Black knots	allowed (filled)	Width 190 mm		
Healthy red heart	not allowed	Length Lengthsystem 5 layers 1900 mm		
Healthy black heart	not allowed ((6 layers pkg) 1 layer 950* mm		
Cracks	allowed (filled)	Connection Tongue and groove Due to the technical drying, there are no longer any pests, only the holes in the middle layer and back. One layer 950* mm consists of 2 boards layer**		
Curled Spots differences in structure	allowed			
Natural colour differences	allowed			
Natural fiber orientation	allowed	m² pkg. 2,17 m² pal. 97,65		
Wormholes and insect-ate-spots	not allowed are allowed in middle layer and back layer**			
Sapwood	partly allowed	kg pkg. 22 kg pal. 990		
Red or brown spots	allowed	\checkmark Floating laying		
Stains from storage and light blueness	allowed	☑ Glued laying		
Knocked spots	not allowed	Suitable for underfloor heating when gluing the entire area with solvent-free adhesives		
Mirror	alongside and crosswise allowed			

