TYPES OF WOOE	ALDER natural steamed - ASH - BEECH natural steamed - BIRCH BLACK WALNUT steamed - CHERRY natural steamed - ELM steamed MAPLE - OAK - PEAR steamed - SMOKED OAK - SMOKED ZIRNOAK	PARKETT
Woodtype	OAK european	
Description	3 layers of the same hardwood. The European Oak has a middle brown to reddish brown colour. The special feature is the occasional occurring sapwood. The sorting Ambiente is slightly to very knotty, with a lively structure.	
Brinell hardness Gross density	4,2 kp 0,71 g cm³	

## 1-Strip Country House Flooring OAK european Ambiente "Lech"



SURFACES

- Oil | Wax oxidative dried
- ☑ Brushed
- Special colour white



## www.bergland-parkett.at

Sorting guidelines			
Healthy knots	allowed (partly filled)		
Black knots	allowed (partly filled)		
Healthy red heart	not allowed		
Healthy black heart	not allowed		
Cracks	allowed (partly filled)		
Curled Spots   differences in structure	allowed		
Natural colour differences	allowed		
Natural fiber orientation	allowed		
Wormholes and insect-ate-spots	not allowed are allowed in middle layer and back layer**		
Sapwood	allowed		
Red or brown spots	allowed		
Stains from storage and light blueness	allowed		
Knocked spots	not allowed		
Mirror	not allowed		

Technical data					
Thickness Width	15 mm 150 mm	Useful layer approx. 5 mm			
Length	Lengthsystem	6 layers 1900 mm			
	(8 layers   pkg)	2 layers 950* mm			
Connection Tongue and groove Due to the technical drying, there are no longer any pests, only the holes in the middle layer and back One layer 950* mm consists of 2 boards layer**					
m² pkg.	2,28	m² pal. 111,72			
kg pkg.	23	kg pal. 1127			
✓ Floating laying					
☑ Glued laying					
Suitable for underfloor heating when gluing the entire area with solvent-free adhesives					

