BLACK WALNUT steamed - CHERRY natural|steamed - ELM steamed

MAPLE - OAK - PEAR steamed - SMOKED OAK - SMOKED ZIRNOAK



Woodtype **ASH** 

3 layers of hardwood. The Ash with heartwood has a light yellow to slightly Description

brownish to prominent dark brown colour. The sorting Design is slightly to very

knotty, with a lively structure.

Brinell hardness 4,5 kp Gross density

0,69 g | cm<sup>3</sup>

The creative program consists of 3 layers hardwood, where the middle layer and the under layer can vary to the top layer.

## 1-Strip Country House Flooring ASH Design Kreativ "Melk"



## **SURFACES**

- Oil | wax oxidative dried
- ✓ Varnished 7-times
- ✓ Untreated sanded
- **✓** Brushed
- **▼** Bevel
- ✓ Special colour



www.bergland-parkett.at

| Sorting guidelines                      |                         |
|---|-------------------------|
| Healthy knots                           | allowed (partly filled) |
| Black knots                             | allowed (partly filled) |
| Healthy red heart                       | allowed                 |
| Healthy black heart                     | allowed                 |
| Cracks                                  | allowed (partly filled) |
| Curled Spots   differences in structure | allowed                 |
| Natural colour differences              | allowed                 |
| Natural fiber orientation               | allowed                 |
| Wormholes and insect-ate-spots          | not allowed             |
| Sapwood                                 | not allowed             |
| Red or brown spots                      | allowed                 |
| Stains from storage and light blueness  | allowed                 |
| Knocked spots                           | not allowed             |
| Mirror                                  | not allowed             |

## Technical data

Thickness 10,7 mm Useful layer approx. 3 mm

Width 150 mm

Length Lengthsystem 7 layers 1900 mm

(11 layers | pkg) 4 layers 950\* mm

Connection Tongue and groove

One layer 950\* mm consists of 2 boards

m<sup>2</sup> | pal. 109,90 m<sup>2</sup> | pkg. 3,14

kg|pkg. 23 kg|pal. 805

✓ Glued laying. Prescribed according to the EU standard. Floating installation is technically possible

✓ Suitable for underfloor heating when gluing the entire area with solvent-free adhesives

